

Skeie | WaveTM

TECHNICAL SPECIFICATION

skeie®

Skeie AS, P.O. Box 4,
N-4301 Sandnes, Norway

T +47 51 97 45 00

F +47 51 97 45 01

E seating@skeie.com

www.skeie.com

Reg.No. NO981505409MVA

DIMENSIONS

Low back, 826 mm:	C/C 500, 520, 550, 580 mm
Medium high back, 930 mm:	C/C 520, 550, 580, 600 mm
High back, 1010 mm:	C/C 520, 550, 580, 600 mm
Extra high back, 1105 mm:	C/C 550, 580, 600 mm

FRAME CONSTRUCTION

ST-37 steel alloy.

4mm supporting steel structure beam, triangle shaped, 91 x 91 x 124mm.

Standard floor fixing is every second chair: 220 x 8 mm steelbracket.

Powder coated steel in standard RAL colors.

The chair is suitable for fixing in the riser and on flat floor in straight rows. Curved rows require a faceted design.

All fixings in chair are metal to metal and floor fixed for every other chair.

SEAT

12mm moulded beech/birch plywood with lacquered edges.

Seat pad is 20mm slab moulded polyurethane foam.

Tip-Up seat with cast steel housing / spring return.

Upholstered inner seat.

SEATBACK

12mm moulded beech/birch plywood with lacquered edges.

Backrest inner padding in 20mm slab moulded polyurethane foam.

Can be delivered without padding and upholstery.

WRITING TABLE

For risers up to 200mm: Fixed writing table to the horizontal beam with steel tube \varnothing 35mm.

For risers over 200mm: Fixed writing table fixed to the floor with steel tube \varnothing 40mm.

Fixed writing table in MDF core with laminate top and lacquered MDF or wood edges.

ADDITIONAL SPECIFICATIONS

Skeie | Wave is certified according to EN 12727, Level 4.

Armrests available in moulded plywood in beech and birch finish.

Other qualities and measurements are available upon request.