

Skeie | Epic Recliner™

TECHNICAL SPECIFICATION

skeie®

Skeie Seating AS,
Svanholmen 19
N-4313 Sandnes, Norway

E: seating@skeie.com
www.skeie.com

Reg.No. NO913369947MVA

DIMENSIONS

High back, 1060mm: cc 560, 600mm, 630mm

Reclineable mechanism for seat and back. Steeltube \varnothing 25 x 2 mm w/ nylon bush and external spring.

FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 25 x 50 x 3 mm.

Standard floor fixing: Flatiron of 70 x 7 mm fixed to rear of the tread.

Powder coated steel in standard RAL colors.

Floor fixing every other chair.

The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.

All fixings in chair are metal to metal.

SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120mm.

Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness center profile max/min 110/65mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated steelframe, optional widths are 70, 110, 140 mm

Cupholder or table mounted to steelframe on armrest available.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Can be delivered without the reclining functionality.

Other qualities and measurements are available upon request.