

Skeie | iNex™

TECHNICAL SPECIFICATION

skeie®

Skeie Seating AS,
Svanholmen 19
N-4313 Sandnes, Norway

–
E: seating@skeie.com
www.skeie.com

Reg.No. NO913369947MVA

DIMENSIONS

High back, 1030mm:

cc 560 mm

Depth, 510mm (580mm with Flex cupholder)

Tip-up mechanism for seat.

FRAME CONSTRUCTION

ST-37 steel alloy.

Main frame 80x30x3.

Powder coated steel in standard RAL colors.

Floor fixing every armrest.

The chair is suitable for fixing on flat floor and in straight or curved rows.

SEAT

Cold moulded polyurethane foam w/ integrated 12mm wood-base. thickness 85mm.

Upholstery sewn to measurements and easily removable with zipper solution.

BACKREST

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness center profile max/min 110/65mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated wood-base. W=70mm

Flex cupholder mounted to wood-base on armrest available.

ADDITIONAL SPECIFICATIONS

Designed and tested according to EN 12727, Level 4.

Row and seat numbers are available.

Can be delivered without the tip-up functionality.